

Keeps Touchup PIs

The `<_nocolumnbreak>` PI is a UDT of `<_touchup>`. The `<_nopagebreak>` PI is likewise a UDT of `<_touchup>`. In an ASCII file, `<_nocolumnbreak>` and `<_nopagebreak>` appear as:

```
<?Pub UDT _nocolumnbreak _touchup KeepsKeep="yes" KeepsPrev="no"
KeepsNext="no" KeepsBoundary="column"?>
```

```
<?Pub UDT _nopagebreak _touchup KeepsKeep="yes" KeepsPrev="no"
KeepsNext="no" KeepsBoundary="page"?>
```

NOTE: These keeps settings are not available in the `<_touchup>` dialog.

Deep content splitting Touchup PI

Arbortext Editor supports **deep content splitting**, which allows page breaks within structures that are too deep for the page, including table rows, boxed areas and `olgroup`-ed columns. When deep content is too deep, a column/page overset results, with the deep content flowing off the bottom of the page.

Deep content splitting can be enabled just for a particular section of a document by selecting it and inserting a `<_deepcontentsplitting>` tag pair. Deep content splitting can also be enabled for all documents; see **Deep content splitting-related ACL** below for details.

NOTE: The `<_deepcontentsplitting>` PI does not apply to Edit window display.

Deep content splitting does not work with:

- Tables with long vertical spans
- Tables with repeating column headings and repeating table footers
- Pages with change bars
- Line numbering
- Table footnotes
- Gentext

Deep content splitting-related ACL

Set `deepcontentsplitting={on | off | never}` controls splitting of deep content. The default is on. An off setting is ignored when a `<_deepcontentsplitting>` tag pair is inserted in a document. Never causes the PI to be ignored,

Deep content splitting example

In this example, deep content splitting is enabled for a portion of a document.

Figure 391 Deep content splitting for part of a document

XML fragment

```
<?Pub _deepcontentsplitting?><reftables>...</reftables>
<?Pub /_deepcontentsplitting?>
```

Touchup examples

Figure 392 shows Touchup PIs in an ASCII file.

Figure 392 Touchup PIs in XML

XML fragment

```
<?Pub _deepcontentsplitting?>...<?Pub /_deepcontentsplitting?>

<?Pub _font Posture="italic" Weight="bold" FontColor="navy"
BackColor="yellow" Underline="single" AllCap="yes" ScoreSpace="yes"?>
Blue foreground yellow background underlined<?Pub /_font?>

as follows:<?Pub _hardspace?>...

T.S.<?Pub _interword-space?>Eliot
To Whom It May Concern—<?Pub _eos-space?>This report...

<?Pub _font TypeSize="48pt" FamName="Arial"?>T
<?Pub _kern Amount="-6pt"?>otal...
```

```
<title>The Loch Ness Monster:<?Pub _newline?>Fact or Fiction</title>
```

```
<paragraph>America's Independence Day is also known as Fourth of July
because <?Pub _nolinebreak?>July 4, 1776<?Pub /_nolinebreak?> ...
```

```
Theo<?Pub _hyphen-point?>dore Roo<?Pub _hyphen-point?>
se<?Pub _hyphen-point?>velt was President...
```

```
<para>The page breaks in this document are set manually
<?Pub _newpage?>in order to...
```

```
...</short-description><?Pub _newcolumn?><specifications>...
```

```
<?Pub _nopagebreak?><sponsors>...</sponsors><?Pub _nopagebreak?>
```

```
<?Pub _nocolumnbreak?><step><note>Be prepared to perform the next
step as soon as you complete this step.</note>...</step><step>...</step>
```